

10/523890

BT01 Rec'd PCT/PTC 04 FEB 2005

CLAIMS

1. Telecommunications and telephony network (AT) for
controlling mobile (TC) or fixed peripheral devices at a
customer premises, of the type comprising at least one
5 local area network, at least one local residents' network
(RLC), at least one regional network, at least one national
network and a central network, said telecommunications and
telephony network (AT) being provided for delivering
signals and data between a plurality of local accesses (AL,
10 AL1), including local users (UL), and a plurality of
networks accesses (AG), through local exchanges (CL, CR),
each of said local exchanges (CL, CR) including a multi-
protocol gateway device (GV) for video and audio signals
and data compression and conversion into IP packets bearing
15 IP telephony data flow or data flow from the Internet and a
local routing device (R) for routing said IP telephony data
flow or data flow from the Internet, wherein said local
users (UL) of each local access (AL, AL1) are connected to
local centralising devices (MD) through first linking means
20 (C0) for flowing data and signals, and said local
centralising devices (MD) are in turn connected to said
local exchanges (CL, CR) through second linking means (C1,
C4) for flowing data and signals, while said local
exchanges (CL, CR) are connected to said networks accesses
25 (AG) through third linking means (C2, C41) for flowing data

and signals, characterised in that at least said second (C1, C4) and said third linking means (C2, C41) are constituted by bidirectional satellite radio bridges (RLD, ST).

5 2. Telecommunications and telephony network (AT) as claimed in claim 1, characterised in that said first linking means (C0) are constituted by physical cables, such as telephone twisted pairs or optical fibers.

10 3. Telecommunications and telephony network (AT) as claimed in claim 1, characterised in that said local routing devices (R) are connected to satellite routing devices (RS) or to radio bridges (PR), said radio bridges (PR) being able to provide connection between local residents' networks (RLC).

15 4. Telecommunications and telephony network (AT) as claimed in claim 1, characterised in that each national network is connected to the relative regional network by means of a digital geostationary satellite network.

20 5. Telecommunications and telephony network (AT) as claimed in claim 1, characterised in that each regional network is connected to the relative local residents' network (RLC) by means of a digital bidirectional satellite radio transmission or by means of communication via optical fibres.